

Pneumatic Forklift Trucks

D60S / D70S-5 & D80S / D90S-5 G60S / G70S-5

6,000kg to 9,000kg Capacity



















G60S / G70S-5 6,000kg 7,000kg LP Gas; Pneumatic Tire



D60S / D70S-5 & D80S / D90S-5 6,000kg 7,000kg 8,000kg 9,000kg Diesel; Pneumatic Tire



Doosan Infracore Forklifts

Head Office: 7-11, Hwasu-Dong, Dong-Gu, Incheon, Korea.
Tel: 82-32-211-5011 Fax: 82-32-211-5412
Seoul Office: 22nd floor, Doosan Tower Bldg, Euljiro 6-Ga Jung-Gu, Seoul, Korea.

Tel: 82-2-3398-8633 Fax: 82-2-3398-8619

Web site : http://iv.doosaninfracore.co.kr/eng AUTHORIZED DEALER

Product and specifications are subject to improvement and change without notice.

PSC0807B2 (July.2008)

Made to Order... For Your Heavy Duty Operation!







To keep drivers running at peak efficiency we've made operator comfort a top priority

Easy-To-Read integrated Instrument Panel

Engine coolant temperature, transmission oil temperature, speed meter, fuel level gauge and hour meter keeps the driver aware of the machine's operating conditions. Engine oil pressure, alternator voltage, water separator gauge and pre-heater illuminates to alert operator to any problem.



Convenience Package

Deck mounted control valve levers simplify hydraulic actuation Convenience tray keeps paperwork and supplies organized and handy.



High Visibility Overhead Guard and Front-end

Wider mast window, repositioned hydraulic hoses and flat bar style overhead guard optimizes operator sight lines forward, up and to the load.



Auto tilt leveling (optional)

Easily returns the mast to upright vertical position with the simple push of a button.



Deluxe Suspension Seat with OSS(Operator Sensing System)

A comfortable deluxe suspension seat with OSS(operator sensing system), a large seatback angle, longer seat travel length and operator's weight resistance on front side allow multiple adjustments for optimum seating comfort.



Spacious Leg Room & Operator Comfort

The neat and wide-open floorboard provides operator with plenty of foot room to make entry and exit a breeze.



Optimum Pedal System(OPS)

This Option Pedal System will reduce the operators fatigue and provide best sense of drivability. Especially, the new electronic accelerator will provide the operator with secure and exact speed control.











Integration of Electrical Components for Easy Maintenance

Fuse and relay box located in front of the engine for easy access and simplified maintenance.



Dual LPG tank and Swing down type LPG cradle

Dual LPG tanks provide plenty of fuel to insure long running shift operations. A swing down LPG bracket simplifies tank installation and removal

DRIVE THE DIFFERENCE...

Doosan forklift trucks are designed with longevity in mind. A Doosan truck has specific design elements that enhance the reliability of its parts for decreased wear and tear and increased endurance. Count on the reliability of Doosan forklift trucks to allow you to concentrate on other aspects of your business besides material handling.

Oil- Cooled Disc Brakes

Oil cooled disc brakes are available on D/G60S-5 & D80S-5 series lift truck and are recommended for applications in humid, abrasive or corrosive environments, or with ramp, loading and unloading applications. This enclosed brake system eliminates outside contamination, significantly extends brake life and decreases maintenance cost. Oil cooled disc brakes have service intervals 5 times longer than conventional shoe brakes, and require little to no maintenance.



Power reversal transmission

Top mounted control valve on the transmission precisely modulates clutch oil pressure for smooth forward / reverse directional changes. Large clutch packs and transmission design permits on-the-go shifting up to 5mph for increased productivity.



Hydrostatic steering system

No mechanical connections between steering wheel and steer axle for reduced maintenance.
8 grease zerks for proper lubrication.
Sealed tapered roller bearings offer protection against contamination and in high impact applications.
Provides low effort steering with quick steering response.



Dual element air cleaner (standard)

Dual element air cleaner brings cool clean air into the engine intake system.




Full floating drive axle

Strong one-piece cast housing keeps axle components aligned. High tensile strength alloy steel axle shafts are carbonized for extended life and splined to the differential side gear & drive wheel hub gears to effectively transmit high torque to the drive wheels.



DRIVE DOOSAN!





● GM V6 4.3L (69 kW)

The highly efficient and powerful GM 4.3L LP Gas engine has time-proven durability.

It's low noise level and minimal vibration will add to operators comfort while the engine provides the forklift with excellent power.



E DOOSAN!




Proven Quality, Responsive Service and A Reliable Partner....


After sales servicing of Doosan forklifts is available from the selling dealership backed by Doosan's own customer service center. And Doosan provides 100% parts inventory to insure any downtime is minimized.

When you own a Doosan forklift, our high quality, responsive customer support team comes with it.

The Doosan network starts with your local dealer and ends with a national team of highly qualified and experienced personnel standing ready to support all your material handling needs.







■ Option Availability

■ Option Availability		● : Sta	ndard 🔾 : Optional	
Options	D60/70S-5	D80/90S-5	G60/70S-5	
Fuel Cap with Key	0	⟨>	n/a	
Precleaner	O	<>	O	
Vertical Exhaust Tube	•	•	O	
Catalytic Muffler	()	O	0	
Air conditioner	O	O	0	
Non Marking Tire(Solid)	()	O	O	
Spark Arrestor(w,w/o C/B)	()	O	n/a	
Mono Ped Foot Direction and Acceleration Control	O	O	0	
AutoShift-2Speed (Single,Dual Tire)*	()	n/a	O	
Engine Shutdown	0	()	O	
Swingdown LP MTG	n/a	n/a	•	
Lift and Tilt locking Hydraulic Control Valve	•	•	•	
Auto Tilt Leveling	()	O	0	
Hydraulic Accumulator	0	O	O	
Intergral fork mover	0	O	()	
Intergral Side shift and forkmover	0	0	()	
Hook on Sideshifter	0	0	O	
UL LPS,DS Rating	0	()	0	

^{*}Autoshift is option for 2Speed Truck only

■ Main Specification

• 3-Speed T/M Truck

	Sales Model		l D60S-5		D70S-5		D80S-5		D90S-5	
Rated Load Capacity	kg 6000		00	7000		8000		9000		
Load Center		mm	600		600		600		600	
Overall Length to Fork Face	L	mm	3568		3647		3970		4040	
Truck Overall Width	W	mm	21	08	21	108	2230		2230	
Height of Overhead Guard	Н	mm	24	55	24	1 55	2648		2648	
Minimum Turning Radius	R	mm	33	31	33	880	3610		3680	
Travel Speed, Loaded / Unloaded		km/h	29.5 / 32.5	30 / 34	29 / 32	29 / 34	30 / 34	30 / 36	28 / 33.5	28 / 35.5
Lifting Speed, Loaded / Unloaded		mm/s	490	/ 530	445	/ 470	430 / 470		430 / 470	
Wheel Base		mm	22	50	22	250	2500		2500	
Engine Models			DB58S	D439E	DB58S	D439E	DB58S	D439E	DB58S	D439E
Rated Power of Engine		kW/rpm	74 / 2200	74 / 2300	74 / 2200	74 / 2300	74 / 2200	74 / 2300	74 / 2200	74 / 2300
Max Torque		N-m/rpm	363 / 1400	373 / 1600	363 / 1400	373 / 1600	363 / 1400	373 / 1600	363 / 1400	373 / 1600
Cylinders / Displacements		сс	6 / 5785	4 / 3900	6 / 5785	4 / 3900	6 / 5785	4 / 3900	6 / 5785	4 / 3900
Transmission type			Auto	Shift	Auto Shift		Auto Shift		Auto Shift	

• 2-Speed T/M Truck

	Sales Model		D60S-5		D70S-5		G60S-5	G70S-5	
Rated Load Capacity	kg		6000		7000		6000	7000	
Load Center	mm		600		600		600	600	
Overall Length to Fork Face	L mm		3568		3647		3568	3647	
Truck Overall Width	W mm		2108		2108		2108	2108	
Height of Overhead Guard	H mm		2455		2455		2455	2455	
Minimum Turning Radius	R mm		3331		3380		3331	3380	
Travel Speed, Loaded		km/h	24.5 / 26.5	23/24.5	24.0 / 26.5	22.5 / 24.5	23.8	23.6	
Lifting Speed, Loaded		mm/s	415 / 445	400 / 430	360 / 390	350 / 380	380	380	
Wheel Base		mm	2250		2250		2250	2250	
Engine Models			DB58S	D439E	DB58S	D439E	G643,G643E	G643,G643E	
Rated Power of Engine	kW/rpm		69 / 2400	68 / 2300	69 / 2400 68 / 2300		69 / 2450	69 / 2450	
Max Torque		N-m/rpm	324 / 1600	324 / 1600	324 / 1600	324 / 1600	297 / 1400	297 / 1400	
Cylinders / Displacements	сс		6 / 5785	4 / 3900	6 / 5785 4 / 3900		6 / 4294	6 / 4294	
Transmission type	Power Shift		Power Shift		Power Shift	Power Shift			